



SEI GIORNI II EDITION 300 HPE - SPECIFICATII TEHNICE

MOTOR	4-valve mono cilindru 4 timpi, injectie electronica, catalizator hpe
CAPACITATE	278 cc
CURSA X ALEZAJ	75 mm x 63 mm
PUTERE MAXIMA LA ARBORELE COTIT	17.5 kW - 23.8 HP – la 8,250 rpm
CUPLU MAXIM	26 Nm at 5,250 rpm
CONSUMUM	3.2 l /100km
NORME EMISII CO2	74 g/km
SISTEM ALIMENTARE	Injectie electronica
RACIRE	Lichid
PORNIRE	Electric
CUTIE VITEZE	CVT automata cu servocuplu
AMBREIAJ	Automatic uscat centrifugal cu amortizoare de soc
STRUCTURA CAROSERIE	Caroserie tabla otel cu structura armaturi sudate
SUSPENSIE FATA	Mono brat cu arc elicoidal și amortizor hidraulic
SUSPENSIA SPATE	Amortizor dublu hidraulic cu arc elicoidal reglabil preincarcare 4 poziții
FRANA FATA	Disc otel Ø 220 mm actionata hidraulic
FRANA SPATE	Disc otel Ø 220 mm actionata hidraulic
SISTEM ABS/ASR	ABS/ASR standard
ANVELOPA FATA	Tubeless 120/70 - 12"
ANVELOPA SPATE	Tubeless 130/70 - 12"
LUNGIME/LATIME/DISTANTA INTRE ROTI	1,950 / 755 / 1,380 mm
INALTIME SA	790 mm
CAPACITATE REZERVOR	8.5 litri
NORME EMISII	Euro 5